

New South Wales / Head Office
2 Wonderland Drive EASTERN CREEK NSW 2766
PH : 02-8805-4000 FAX : 02-8805-4248

Queensland
23 Terrace Place MURARRIE QLD 4172
PH : 07-3908-9000 FAX : 07-3399-4179

Victoria
3 John Deere Court, Parkwest Estate DERRIMUT VIC 3030
PH : 03-8369-0900 FAX : 03-9931-0677

South Australia
91 Transport Avenue NETLEY SA 5037
PH : 08-8238-0200 FAX : 08-8238-0299

Western Australia
Unit 1/1A 2 Business Way Malaga 6090
PO Box 1724 Malaga WA 6944
PH : 08-9249-3721 FAX : 08-9249-1300

Customer Information Centre is available 7 days
from 7AM-7PM on 1300 54 2273 (1300 LG CARE)
SMS Fault call 0400 660 629
<http://www.lg.com.au/airconditioning>

NEW ZEALAND
Unit A, 38 Highbrooke Drive, East Tamaki, 2013 New Zealand
Tel : +64 (09) 914 2444 Fax : +64 (09) 914 2441
Customer Service Helpline
0800 54 2273 (0800 LG CARE)
www.lg.co.nz

Warranty Brief

- Multi F/ Multi Fdx Air Conditioning Units are covered by a 5-Year Parts and Labour Warranty when used in Residential Applications. Commercial Applications attract a 2-Year Parts and Labour Warranty.*
- Air Conditioning units carry an on-site warranty.*

*Further conditions apply, see the Warranty Card for further information.

Due to LG's policy of continuous improvement and innovation, some specifications may change without notice.

Please check with your retailer / AC specialist prior to purchase.
© LG Electronics Australia Pty., Ltd. Printed in Korea [March 2012]



LG Electronics Changwon Facility Achieved ISO9001 Certification Under Series 9000 of International Standard Organization(ISO) Based on Quality Systems For Design & Manufacture of Air Conditioners, Hermetic Refrigeration Compressors.



LG Multi Split Air Conditioners

Enjoy Clean, Stylish and Comfortable Air Conditioning with LG

Disclaimer

The descriptions and specifications in this brochure are relevant as at the date of publication. In the interest of product development, LG Electronics reserves the right to carry out alterations and improvements to products and specifications. Future releases of products, accessories and parts for them may differ from, and may not be compatible with current versions. As it may be difficult to determine the exact nature of a product from its depiction in this brochure, LG Electronics strongly recommends that you confirm with your retailer that the product shown or described in this brochure meets your requirements before you purchase the product.

Enjoy Clean, Stylish and Comfortable Air Conditioning with LG

LG is committed to bringing comfort to its customers and has produced a large range of air conditioners that do just that. It's all about comfort in the home, and offering you the perfect harmony of stylish design and smart technology that fits your life.

Whether it is just a small unit for the bedroom, a larger unit to help keep you cool in your lounge room, or a system to cool the entire house such as Ducted or Multi-Split systems, LG has designed stylish, smart, reliable and functional air conditioners designed to help make **Life good**.



Milestone

1958	Company founded
1968	Manufactured Korea's first air conditioner
1985	Introduced Korea's first inverter air conditioner
1990	Produced rotary compressor
1995	Changed company name to LG Electronics Produced scroll compressor
1998	Produced Korea's first commercial air conditioner
2000	Became world's number one seller of residential air conditioners
2001	Introduced the world's first picture frame air conditioner
2002	Launched the LG Home Net Brand of integrated home networking solution
2004	Achieved world's highest annual sales in air conditioners with 10 million units
2008	Reached total global sales of 100 million air conditioners
2009	AC Company created as part of LG Electronics' business reorganization

LG Multi Split Air Conditioners

Why? LG Multi System.....	4
Remove outdoor unit from the balcony	
LG Air conditioners suitable for multi system	
Inverter Technology	
Wide Range of Units	
Indoor Capacity Combination	
Outdoor Units	9
Available Outdoor Unit Capacity	
Combination of indoor and outdoor unit	
Specifications	
Indoor Units	14
Wall Mounted	
Ceiling Cassette	
Ceiling Concealed Duct	
Combination Table	20
Accessory	29
Distributor Box	
Accessory	

Why The LG Multi Split?

An LG Multi Split system is an advanced air conditioning system of superior quality that has the ability to operate at different temperatures and fan speeds in individual rooms. The multi split system can be made up of large indoor units for living areas and small indoor units for bedrooms, all operated from the one common outdoor unit. LG has a wide range of indoor units available including the stylish ArtCool units, conventional split units as well as cassette and ducted units.

- **Wide Range of Unit Combinations**

8 different types of indoor units
7 different capacity outdoor units

- **Energy Efficient**

An inverter's capacity will vary to match the air conditioning requirements, so an inverter can be more energy efficient than a fixed speed compressor as it does not stop and start its motor continually.

- **Wide Range of Unit Combinations**

Various controls available, such as Touch panel wall controller, Central controller and Control via the internet.

- **Max. 145m Long Piping**

The UHXM170BA0 supports a total piping length of up to 145m and high elevation of up to 30m for more flexibility in installation.

- **High combination of indoor unit**


Indoor unit combination up to 180% of outdoor unit capacity (k Btu index)

- **Compact Size & Easy Installation**

The reduced chassis size on UHXM90BA0 creates a more compact unit and is easier to install.

Remove outdoor unit from the balcony

The long pipe run of up to 45m allows LG outdoor units to be placed on the roof, in the car park or in the common outdoor unit plant room freeing up on balcony.




UHXM90BA0 (8.8 kw)

– 45m pipe run/ 15m Elevation

For low and medium rise apartments*

Remove outdoor units from balcony and move to the roof, car park or common plant room in the apartments.

- Aesthetics
- More living space on the balcony



UHXM170BA0

–145m total pip run/30m elevation

For high and medium rise apartments*



*1. Maximum number of floors is subject to the height between floors.

*2. Consult with specialist to install outdoor units on the roof, in the car park or in the plant room.



LG Air conditioners suitable for multi system



ART COOL Mirror



ART COOL Gallery



Wall Mounted Type



Ceiling Concealed Duct Type



1-way Ceiling Cassette Type




4-way Ceiling Cassette Type

MULTI F



MULTI F DX



Energy Efficiency




What is Inverter Technology?

Inverter technology refers to the compressor within the outdoor unit of the air conditioner. An inverter compressor will vary its speed in order to maintain a consistent room temperature.

POWERFUL

With a wide operational temperature range for heating and cooling, the inverter is able to operate in even extreme outdoor temperatures. An inverter compressor can also operate quickly thus allowing the air conditioner to reach the set temperature faster and bring you comfort sooner.



COMFORTABLE

When the air conditioner is initially activated to either heat or cool, the compressor will operate at maximum speed to reach the desired temperature quickly. Once the desired temperature is achieved, LG inverter units adjust and constantly vary the compressor speed to maintain the desired temperature with minimal fluctuation in room temperature to ensure that your comfort is not compromised.

Inverter Technology

ECONOMICAL

An inverter's capacity will fluctuate in order to match the air conditioning requirements, so an inverter can be energy efficient, as it does not stop and start its motor continually.

QUICK COOLING & HEATING

Inverter air conditioners can operate their compressors faster to give them more powerful performance. This results in being able to attain the desired temperature much faster in both heating and cooling modes.

Wide Range of Units


Wide Range of Outdoor Units



Wide Range of Indoor Units



Indoor Capacity Combination



*Max combination:
the percentage of total capacity index sum of indoor units connected to an outdoor unit against outdoor unit capacity index (Btu/h)

Outdoor Unit

Long & High Elevation Piping


The UHXM170BA0-U30 supports a piping length of up to 145m and high elevation of up to 30m for more flexibility in installation.

MULTI F (Multi piping Type)

Piping Length (m)	UHXM55MA	UHXM70MA0	UHXM90MA0
Total	50	70	75
Max/Room	25	25	25
Allowable Elevation (Indoor~Outdoor)	15	15	15
(Indoor~Indoor)	7.5	7.5	7.5


Wide Operating Range

Using LG inverter technology, LG Multi achieves a wide range of capacity which is from 25% ~ 120% in cooling mode and from 25% ~ 120% in heating mode to facilitate faster cooling and heating. The LG multi system achieves operation up to Max. ambient conditions of 46°C in cooling mode and down to -10°C in heating mode.




MULTI F DX (1 Phase) (Distributor box Type)

	UHXM90BA0	UHXM120BA0	UHXM160BA0	UHXM170BA0
Total Pipe (A+L1+L2+L3)	80	100	135	145
Main Pipe (A)	30	50	55	55
Total Branch Pipe (L1+L2+L3)	50	50	80	90
Each Branch Pipe	15	15	15	15
Allowable Elevation Indoor~Outdoor (B)	15	30	30	30
Indoor~Indoor (C)	7.5	15	15	15



Slim & Compact Outdoor Unit

Easy & efficient installation of outdoor unit will provide the best solution for small offices and shops in addition to apartments.




Available Outdoor Unit Capacity

Power	Max Indoor Units	Capacity Range (k Btu index/kW)					
		18/5.3	24/7.0	30/8.8	40/11.7	48/15.5	56/16.7
MULTI F 1ø, 220-240V, 50Hz	3	●					
	4		●				
	5			●			
MULTI F DX 1ø, 220-240V, 50Hz	4			●			
	7				●		
	8					●	
	9						●

MULTI F



MULTI F DX



Combination of indoor and outdoor unit

Indoor units		Capacity Range (k Btu index/kW)	UHXM55MA0	UHXM70MA0/ UHXM90MA0 UHXM90BA0/ UHXM120BA0	UHXM160BA0 / UHXM170BA0
Wall Mounted Type	Wall Mounted 	7 / 2.1	●	●	●
		9 / 2.6	●	●	●
		12 / 3.5	●	●	●
		18 / 5.3	●	●	●
		24 / 7.0	-	●	●
	ART COOL Gallery 	9 / 2.6	●	●	●
		12 / 3.5	●	●	●
	ART COOL Mirror 	7 / 2.1	●	●	●
		9 / 2.6	●	●	●
		12 / 3.5	●	●	●
		18 / 5.3	●	●	●
		24 / 7.0	-	●	●
Ceiling Cassette Type	1-way 	9 / 2.6	●	●	●
		12 / 3.5	●	●	●
	4-way 	12 / 3.5	●	●	●
		18 / 5.3	●	●	●
		24 / 7.0	-	●	●
		30 / 8.2	-	-	●
Ceiling Concealed Duct Type	High static pressure 	18 / 5.3	●	●	●
		24 / 7.0	-	●	●
		30 / 8.8	-	-	●
	Low static pressure 	36 / 10.6	-	-	●
		9 / 2.6	●	●	●
		12 / 3.5	●	●	●
	Slim Low Static 	18 / 5.3	●	●	●
		9 / 2.6	●	●	●
		12 / 3.5	●	●	●
		18 / 5.3	●	●	●
		24 / 7.0	-	●	●

Specifications - Outdoor Units

MULTI F Inverter 1Phase



UHXM55MA0
UHXM70MA0



UHXM90MA0

Model			UHXM55MA0	UHXM70MA0	UHXM90MA0
Max. Number of Connectable Indoor Units			3	4	5
Capacity (Min~Rated~Max)	Cooling	kW	1.35~5.30~6.33	1.85~7.03~8.50	1.85~8.80~10.55
	Heating	kW	1.41~6.30~7.27	2.22~8.44~9.38	2.22~10.10~12.10
Power Input (Min~Rated~Max)	Cooling	kW	0.38~1.20~2.37	0.72~1.75~3.09	0.72~2.31~3.16
	Heating	kW	0.45~1.31~2.48	0.88~1.83~3.10	0.88~2.19~3.87
EER	Cooling	kW	4.42	4.02	3.81
COP	Heating	kW	4.81	4.61	4.61
Testing Combination			MS07AH x 3EA	MS07AH x 4EA	MS07AH x 5EA
Running Current (Min~Rated~Max)	Cooling	A	1.70~5.23~10.30	3.10~7.65~13.40	3.10~10.10~13.70
	Heating	A	2.00~5.70~10.80	3.80~8.00~13.50	3.80~9.60~16.80
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable (outdoor)	No. x mm ²		3 x 2.50	3 x 2.50	3 x 2.50
Power and transmission cable (outdoor to indoor)	No. x mm ²		4 x 0.75 (Including earth)	4 x 0.75 (Including earth)	4 x 0.75 (Including Earth)
Dimensions	W*H*D		870x808x320 (34.30x31.80x12.60)	870x808x320 (34.30x31.80x12.60)	950x834x330 (37.40x32.80x13.00)
Net Weight	kg(lbs)		58 (128.00)	61 (134.00)	67 (147.70)
	Charge (at 7.5m)	g(oz)	2,100 (74.10)	2,300 (81.13)	3,300 (116.40)
	Type		R410A	R410A	R410A
Refrigerant	Control		EEV	EEV	EEV
	I/s		883	883	1,000
Noise Level	Sound Pressure at 1m	dB(A)+3	52	52	53
	Sound power	dB(A)+3	63	63	63
Piping connections	Liquid(ø)	mm(inch)	6.35(1/4)x3EA	6.35(1/4)x4EA	6.35(1/4)x5EA
	Gas(ø)	mm(inch)	9.52(3/8)x3EA	9.52(3/8)x4EA	9.52(3/8)x5EA
Max. Interunit Piping Length	Total piping	m	50	70	75
	For One Room	m	25	25	25
Max. Elevation	Indoor Unit~Outdoor Unit	m	15	15	15
	Indoor Unit~Indoor Unit	m	7.50	7.50	7.50
Operating temperature	Cooling	°C	-10 ~+46	-10 ~+46	-10 ~+46
	Heating	°C	-10 ~+24	-10 ~+24	-10 ~+24

Note : 1. Capacities are based on the following conditions: Cooling: - Indoor Temperature 27°C DB /19 °C WB
- Outdoor Temperature 35°C DB /24°C WB
Heating: - Indoor Temperature 20°C DB / 15°C WB
- Outdoor Temperature 7°C DB / 6°C WB
Piping Length - Interconnecting Piping Length 7.5m
- Level Difference of Zero.

2. *: See page "Combination Table" 20~28 Page.
3. Due to our policy of innovation some specifications may be changed without notification.
4. Number of indoor units connected to outdoor unit must be 2 units or more

*For derated capacity at other ambient conditions pls refer to Engineering Product Data Book.

MULTI F DX Inverter 1Phase



UHXM90BA0



UHXM120BA0



UHXM160BA0
UHXM170BA0

Model			UHXM90BA0	UHXM120BA0	UHXM160BA0	UHXM170BA0
Max. Number of Connectable Indoor Units			4	7	8	9
Capacity (Min~Rated~Max)	Cooling	kW	1.85~8.80~10.55	2.80~11.70~13.50	3.30~15.50~17.00	4.00~16.70~18.52
	Heating	kW	2.22~10.10~12.10	3.20~13.50~15.00	3.70~16.40~17.29	4.50~17.90~18.75
Power Input (Min~Rated~Max)	Cooling	kW	0.72~2.50~3.16	1.10~3.63~4.65	0.84~4.69~5.35	1.00~4.96~5.65
	Heating	kW	0.88~2.30~3.87	1.40~3.65~4.84	1.30~4.43~5.58	1.25~4.62~5.70
EER	Cooling	kW	3.52	3.22	3.30	3.37
COP	Heating	kW	4.39	3.70	3.70	3.87
Testing Combination			MS12AH x 4EA	MS09AH x 7EA	MS07AH x 5EA MS09AH x 3EA	MS09AH x 8EA
Running Current (Min~Rated~Max)	Cooling	A	3.10~10.90~13.70	6.20~16.00~20.00	3.90~21.10~23.20	4.60~21.70~24.00
	Heating	A	3.80~10.10~16.80	6.90~16.40~20.50	6.90~22.60~25.00	7.40~22.40~26.00
Power Supply	Ø / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable (outdoor)	No. x mm ²		3 x 2.50 (Including Earth)	3 x 3.50 (Including Earth)	3 x 4.00 (Including Earth)	3 x 4.00 (Including Earth)
Power and transmission cable (outdoor to BD)	No. x mm ²		4 x 1.25 (Including earth)	4 x 1.25 (Including Earth)	4 x 1.25 (Including Earth)	4 x 1.25 (Including Earth)
Power and transmission cable (BD to indoor)	No. x mm ²		4 x 0.75 (Including earth)	4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)
Dimensions	W x H x D	mm(inch)	950 x 834 x 330 (37.40 x 32.80 x 13.00)	900 x 1165 x 370 (35.40 x 45.80 x 14.50)	950 x 1380 x 330 (37.40 x 54.30 x 13.00)	950 x 1380 x 330 (37.40 x 54.30 x 13.00)
Net Weight	kg(lbs)		64 (141.10)	95 (209.00)	108 (238.00)	108 (238.00)
Refrigerant	Charge (at 7.5m)	g(oz)	2,750(97.0)	4,000 (141.10)	4,800 (169.30)	4,800 (169.30)
	Type		R410A	R410A	R410A	R410A
	Control		EEV	E.E.V	E.E.V	E.E.V
Air Flow Rate	I/s		883	883 x 2	1,000 x 2	1,000 x 2
Noise Level(H/L)	Sound Pressure at 1m	dB(A)+3	52	58	58	59
	Sound power	dB(A)+3	63	66	69	70
Piping connections	Liquid(ø)	mm(inch)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)
	Gas(ø)	mm(inch)	15.88 (5/8)	19.05 (3/4)	19.05 (3/4)	19.05 (3/4)
Max. Interunit Piping Length	Total Piping (Main+Total Branch)	m	80	100	135	145
	Main Piping	m	30	50	55	55
	Total Branch Piping	m	50	50	80	90
	Each Branch Piping	m	15	15	15	15
Max. Elevation	Indoor Unit~Outdoor Unit	m	15	30	30	30
	Indoor Unit~Indoor Unit	m	7.50	15.00	15.00	15.00
Operating temperature	Cooling	°C	-10 ~+46	-10 ~+46	-10 ~+46	-10 ~+46
	Heating	°C	-10 ~+24	-10 ~+24	-10 ~+24	-10 ~+24

Note : 1. Capacities are based on the following conditions: Cooling: - Indoor Temperature 27°C DB /19 °C WB
- Outdoor Temperature 35°C DB /24°C WB
Heating: - Indoor Temperature 20°C DB / 15°C WB
- Outdoor Temperature 7°C DB / 6°C WB
Piping Length - Interconnecting Piping Length 7.5m
- Level Difference of Zero.

2. *: See page "Combination Table" 20~28 Page.
3. Due to our policy of innovation some specifications may be changed without notification.
4. Number of indoor units connected to outdoor unit must be 2 units or more

*For derated capacity at other ambient conditions pls refer to Engineering Product Data Book.



Indoor Unit - Wall Mounted

Capacity (kW)		2.1	2.6	3.5	5.3	7
	Wall Mounted	MS07AH	MS09AH	MS12AH	MS18AH	MS24AH
	ART COOL Gallery		MA09AH NF1	MA12AH NF1		
	ART COOL Mirror	NHXM20S2A0	NHXM30S2A0	NHXM40S2A0	NHXM50S2A0	NHXM70S2A0

Neo-Plasma Air Purifying System

LG's unique Neo Plasma Air Purifying System has been designed to generate fresher and cleaner air. Made up of 8 filters which purify the air in 6 stages, where each stage of the filtration acts to reduce odours and fine dust particles from the environment .



Low Indoor Noise Level

The indoor unit has a quiet operational noise level in sleep mode to offer you peace and quiet for your bedroom or office.



Wall Mounted		MS07AH	MS09AH	MS12AH	MS18AH	MS24AH
Cooling Capacity	kW	2.05	2.64	3.52	5.28	6.74
Heating Capacity	kW	2.34	2.93	3.87	5.80	7.47
Running Current	A	0.10	0.15	0.15	0.28	0.28
Air flow rate (H/M/L)	l/s	93/83/77	117/108/100	158/150/142	200/175/150	233/217/183
Dimensions (WxHxD)	Body	mm(inch) 840x270x153 (33.10x10.60x6.02)	840x270x153 (33.10x10.60x6.02)	840x270x153 (33.10x10.60x6.02)	1090x300x180 (42.90x11.80x7.08)	1090x300x180 (42.90x11.80x7.08)
Weight	Body	kg	7	7	13	13
Sound level (H/M/L) (Sound pressure at 1.0m)		dB(A)+3	29 / 25 / 20	33 / 29 / 22	36 / 32 / 29	37 / 34 / 31
Piping connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	12.70 (1/2)
Dehumidification rate	l/h	0.90	1.10	1.20	2.30	3.00

ART COOL Gallery		MA09AH NF1	MA12AH NF1
Cooling Capacity	kW	2.64	3.52
Heating Capacity	kW	2.93	3.87
Running Current	A	0.08	0.08
Air flow rate (H/M/L)	l/s	128/98/73	148/122/93
Dimensions (WxHxD)	Body	mm(inch) 600x600x146 (23.60x23.60x5.70)	600x600x146 (23.60x23.60x5.70)
Weight	Body	kg	15
Sound level (H/M/L) (Sound pressure at 1.0m)		dB(A)+3	44 / 38 / 32
Piping connections	Liquid	mm(inch)	6.35 (1/4)
	Gas	mm(inch)	9.52 (3/8)
Dehumidification rate	l/h	1.20	1.40

ART COOL Mirror		NHXM20S2A0	NHXM30S2A0	NHXM40S2A0	NHXM50S2A0	NHXM70S2A0
Cooling Capacity	kW	2.05	2.64	3.52	5.28	6.74
Heating Capacity	kW	2.34	2.93	3.87	5.80	7.47
Running Current	A	0.10	0.15	0.15	0.28	0.28
Air flow rate (H/M/L)	l/s	133/117/83	167/133/100	167/133/100	210/192/167	250/233/217
Dimensions (WxHxD)	Body	mm(inch) 915x282x165 (36.00x11.10x6.50)	915x282x165 (36.00x11.10x6.50)	915x282x165 (36.00x11.10x6.50)	1107x299x200 (43.60x11.80x7.90)	1107x299x200 (43.60x11.80x7.90)
Weight	Body	kg	9.5	9.5	14.1	14.1
Sound level (H/M/L) (Sound pressure at 1.0m)		dB(A)+3	34/29/26	35/30/27	39/37/35	43/41/38
Piping connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	9.52 (3/8)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)
Dehumidification rate	l/h	1.00	1.20	1.50	2.00	2.50



SLIM 1 WAY CASSETTE

The slim 1 way cassette indoor unit is one solution for apartment bed room application due to its low height which can be suitable for low ceiling spaces.



4 WAY CASSETTE

4 Vane Independent Operation

Vane angle control satisfies both users who like direct wind or indirect wind and it also reduces cold air drafts. One motor per vane is used to control each of the four vanes independently, freely controlling air currents according to your requirements.

4 Corners Detachable Panels

The attachable/detachable corner design makes it easy to adjust the hanger during installation and to check for leakage in the drain connection pipe.

Fresh air intake kit
(NHXM70C4A0, NHXM80C4A0,NHXM110C4A0 only)

Using this kit, a duct can be fitted to allow the intake of outdoor air.

Slim & Compact size

The indoor unit with slim and compact size enables successful installation in confined spaces.

Indoor Unit - Ceiling Cassette

Capacity (kW)		2.6	3.5	5.3	7.0	8.8	10.5
	1-Way	NHXM30C1A0	NHXM40C1A0				
	4-Way		NHXM40C4A0	NHXM50C4A0	NHXM70C4A0	NHXM80C4A0	NHXM110C4A0

1-Way			NHXM30C1A0	NHXM40C1A0	
Cooling Capacity			kW	2.64	3.52
Heating Capacity			kW	2.93	3.87
Running Current			A	0.56	0.56
Air flow rate (H/M/L)			l/s	142/125/108	158/133/117
Dimensions (WxHxD)	Body	mm(inch)	860x180x390 (33.80x7.10x15.30)	860x180x390 (33.80x7.10x15.30)	
	Decorative panel	mm(inch)	1050x30x480 (41.30x1.20x18.90)	1050x30x480 (41.30x1.20x18.90)	
Weight	Body	kg	22	22	
	Decorative panel	kg	4	4	
Sound level (H/M/L) (Sound pressure at 1.5m)			dB(A)+3	35 / 32 / 28	37 / 33 / 29
Piping connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	
	Gas	mm(inch)	9.52 (3/8)	9.52 (3/8)	
Dehumidification rate			l/h	1.10	1.30
Facial panel name			PT-HCC	PT-HCC	

4-Way			NHXM40C4A0	NHXM50C4A0	NHXM70C4A0	NHXM80C4A0	NHXM110C4A0
Cooling Capacity		kW	3.52	5.28	7.03	8.20	10.60
Heating Capacity		kW	3.87	5.80	7.74	9.00	11.60
Running Current		A	0.35	0.43	0.60	1.15	1.35
Air flow rate (H/M/L)		l/s	158/133/108	217/200/167	283/250/217	317/288/245	400/358/317
Dimensions (WxHxD)	Body	mm(inch)	570x214x570 (22.40x8.40x22.40)	570x256x570 (22.40x10.00x22.40)	840x204x840 (33.10x8.00x33.10)	840x204x840 (33.10x8.00x33.10)	840x246x840 (33.10x9.70x33.10)
	Decorative panel	mm(inch)	700x30x700 (27.50x1.20x27.50)	700x30x700 (27.50x1.20x27.50)	950x25x950 (37.40x1.00x37.40)	950x25x950 (37.40x1.00x37.40)	950x25x950 (37.40x1.00x37.40)
Weight	Body	kg	14.0	15.0	20.8	20.8	23.5
	Decorative panel	kg	3	3	5	5	5
Sound level (H/M/L) (Sound pressure at 1.5m)		dB(A)+3	35/31/27	40/37/34	39/37/34	43/40/37	43/40/38
Piping connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)	15.88 (5/8)	15.88 (5/8)
Dehumidification rate		l/h	1.20	2.40	3.00	3.00	4.00
Facial panel name			PT-UQC	PT-UQC	PT-UMC	PT-UMC	PT-UMC



Indoor Unit - Ceiling Concealed Duct

Capacity (kW)		2.6	3.5	5.3	7.0	8.8	10.5
	Slim Low Static	NHXM30D3A0	NHXM40D3A0	NHXM50D3A0	NHXM70D3A0		
	High Static			NHXM50D1A0	NHXM70D1A0	NHXM90D1A0	NHXM110D1A0

E.S.P: External Static Pressure

EZ Tuning ensures that the air conditioning system operates at its specified performance regardless of changes in ESP (External Static Pressure) by allowing the adjustment and control of fan speed at installation. This results in being able to obtain and maintain the required air flow rate.



Drain Pump

An auxiliary condensate drain pump is available as an option for all LG ducted indoor units. This is an ideal solution where drain fall is limited or unavailable. This will lift water up to a 700mm height above the drain outlet.



Slim duct

The LG slim ducted fan coil unit is a good solution for Apartments or Hotel rooms with lower ceiling space with the height of 190mm for 2.6kw up to 7.0kw.

The drain pump is fitted standard to drain condensate water out Where drain gradient is not enough.



New wired remote controller

- Operating mode (On_Off/Fan speed/Mode/Temp.)
- On / Off LED • Room temp. • E.S.P function
- Reservation (Weekly / Simple) • Timer function • Backlight Unit
- Child lock • Electric failure compensation (Max 3 hours)
- Main / Sub setting of indoor units (For override function)
- Group and central control at the same time



LCD backlit display
Enables you to easily see
the control settings.

Slim Low Static		NHXM30D3A0	NHXM40D3A0	NHXM50D3A0	NHXM70D3A0
Cooling Capacity	kW	2.64	3.52	5.27	7.03
Heating Capacity	kW	2.93	3.87	5.80	7.44
Running Current	A	1.02	1.02	1.60	1.60
Air flow rate (H/M/L)	l/s	142/125/108	158/142/125	250/225/192	283/250/225
External static pressure	Pa	40	40	40	30
Dimensions (WxHxD)	Body	mm(inch)	mm(inch)	mm(inch)	mm(inch)
		820 x 190 x 575 (32.3 x 7.5 x 22.6)	820 x 190 x 575 (32.30 x 7.50 x 22.60)	1,100 x 190 x 575 (43.30 x 7.50 x 22.60)	1,100 x 190 x 575 (43.30 x 7.50 x 22.60)
Weight	Body	kg	20.5	26.5	27.0
Sound level (H/M/L) (Sound pressure at 1.5m)	dB(A)+3	31/26/25	33/31/26	34/31/29	36/34/32
Piping connections	Liquid	mm(inch)	6.35(1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	9.52(3/8)	9.52 (3/8)	12.70 (1/2)
Dehumidification rate	l/h	1.00	1.20	2.00	2.50
Supply spigot (WXH)	mm	794x161	794x161	1072x161	1072x161
Return spigot (WXH)	mm	728x154	728x154	1008x154	1008x154

High Static		NHXM50D1A0	NHXM70D1A0	NHXM90D1A0	NHXM110D1A0
Cooling Capacity	kW	5.28	7.03	8.79	10.6
Heating Capacity	kW	5.80	7.74	9.67	11.6
Running Current	A	0.75	0.75	2.35	2.35
Air flow rate (H/M/L)	l/s	275/242/217	300/275/233	442/383/333	533/483/433
External static pressure	Pa	80	80	100	100
Dimensions (WxHxD)	Body	mm(inch)	mm(inch)	mm(inch)	mm(inch)
		880x260x450 (34.60x10.20x17.70)	880x260x450 (34.60x10.20x17.70)	1180x298x450 (46.50x11.70x17.70)	1180x298x450 (46.50x11.70x17.70)
Weight	Body	kg	31.0	31.2	38.0
Sound level (H/M/L) (Sound pressure at 1.5m)	dB(A)+3	36 / 34 / 32	38/36/34	40/38/35	42/39/36
Piping connections	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm(inch)	12.70(1/2)	12.70 (1/2)	15.88 (5/8)
Dehumidification rate	l/h	2.00	2.50	3.30	4.00
Supply spigot (WXH)	mm	750x158	750x158	830x186	830x186
Return spigot (WXH)	mm	745x175	745x175	1043x220	1043x220

Accessory

Individual control system -Wired remote controller

Deluxe type

Function	Applicable Indoor Type
• On/off, fan speed, mode, temperature • Room temperature • Fan, plasma, swirl swing • Automatic • Vane control • ESP function • Reservation(simple/weekly) • Simple reservation • Timer function • Auto swing, child lock • LCD back-light	Ceiling cassette Ceiling concealed duct



PQRCUDS0

Central control system

Simple central controller+ Function controller

Function	Applicable Indoor Type
• Individual operation (one button one A/C) - On operation (Max. 16 indoors) - Off operation (Max. 16 indoors) - Individual lock function (1 unit) • Group operation - Group On_Off - Group lock function (1 unit) • Sequential starting to protect over current • Diagnostic function (LED blinking)	Wall mounted ART COOL ART COOL mirror Ceiling cassette Ceiling concealed duct



PQCSB101S0
PQCSC101S0

• Mode / Fan Speed / Temperature Control • Indoor Error Display • Total cycling status indication via LCD • Max. 8 groups with 128 units in group control	
---	--

Simple central controller+ Scheduler

Function	Applicable Indoor Type
• Individual operation (one button one A/C) - On operation (Max. 16 indoors) - Off operation (Max. 16 indoors) - Individual lock function (1 unit) • Group operation - Group On_Off - Group lock function (1 unit) • Sequential starting to protect over current • Diagnostic function (LED blinking)	Wall mounted ART COOL ART COOL mirror Ceiling cassette Ceiling concealed duct



PQCSB101S0
PQCSD130A0

• Mode / Fan Speed / Temperature Control • Indoor Error Display • Total cycling status indication via LCD • Max. 8 groups with 128 units in group control • Schedule : Weekly	
---	--

*1 function controller or scheduler can be combined with 8 simple central controllers.

Central control system

AC Smart II

Function	Applicable Indoor Type
• 64 indoor units connection • Option to connect 128 indoor units using expansion kit • Schedule Wizard function • New GUI • Option Kit control : - Web schedule + Power consumption statistics function (PQCSE342A0) - Web schedule function (PQCSE341A0) - Web based schedule setting function - Power consumption statistics function	Wall mounted ART COOL ART COOL mirror Ceiling cassette Ceiling concealed duct



PQCSW320A1E
PQCSE341A0 (Web schedule option kit)
PQCSE342A0 (PDI+ Web schedule option kit)


ACP & AC Manager

Function	Applicable Indoor Type
• Control / Monitoring • Schedule • History - Peak Power Control - PDI Monitoring • Setting - Max 256 Indoor units - Without IO (Install with AC Manager, Interlocking is impossible)	Wall mounted ART COOL ART COOL mirror Ceiling cassette Ceiling concealed duct



PQCPA11A0E (Without IO)
PQCPB11A0E (With IO)
PQCSS520A0E (AC Manager)

AC SMART II



Accessory

Control device - BNU_BN

BACNET for BMS

Function	Applicable Indoor Type
- On/Off command - Operation mode setting - Fan Speed setting - Lock setting - Air flow setting - Set temp. setting - User mode setting (for only ventilator)	Wall mounted ART COOL ART COOL Mirror Ceiling concealed duct Ceiling cassette
	 PQNF17B0

PDI (Power distributor indicator)

PDI (Power distributor indicator)

Function	Applicable Indoor Type
- Accumulated amount of power used indicated - Accumulated amount of power used/current amount used indicated - Accumulated amount of power used by month indicated - Power failure-proof device	Wall mounted ART COOL ART COOL Mirror Ceiling concealed duct Ceiling cassette
	 PQNUD1500

Product interface units

PI485

Function	Applicable Indoor Type
Interface central controller to outdoor unit	
	 PMNFP14A0

Dry_contact

Function	Applicable Indoor Type
- Key Switch - Door Check - Fire Alarm - Motion Detect Sensor - Time clock - Interact with fresh air fan	Wall mounted ART COOL ART COOL Mirror Ceiling concealed duct Ceiling cassette
	 PQDSA (240V) PQDSA1 (24V)
	 PQDSB (240V) PQDSB1 (24V)

Mechanical

Drain Pump Kit



Function	Applicable Indoor Type
- In some places where natural drainage is not possible The drain pump is very useful to pump out condensed water from indoor unit. - Drain pump assembly(AC 220-240V, 50/60Hz)	Ceiling Concealde Duct • ABDPT (for low static type) • ABDPG (for high static type)
	 ABDPT
- In some places where natural drainage is not possible The drain pump is very useful to pump out condensed water from indoor unit. - Drain pump assembly(AC 220-240V, 50/60Hz)	
	 ABDPG

Fresh Air Kit

Function	Applicable Indoor Type
Fresh Air Kit for Cassette	Ceiling Cassette -4way (7.0~10.5kW)
	 PTVK410
Fresh Air Kit for Cassette	Ceiling Cassette -4way (7.0~10.5kW)
	 PTVK420

Piping

Y Branch

Function	Applicable Indoor Type
- Y Branch and Branch kit make Multi Fdx installation much easier. - Y-Branch and Branch kit for both gas and liquid are provided. - Insulation material is also provided for covering the branches.	Outdoor
	 PMBL5620
	 PMBL1203F0

Memo

Memo